

Moulding Tape HS HIGH-BOND TAPE

INDUSTRIAL PRODUCTS

A UNIQUE GREY FOAMED ACRYLIC.



For further information or special applications contact manufacturer :

ChemTechniek Nederland BV De Smalle Zijde 40a 3903 LP Veenendaal

Telephone: +31-318-821521
Telefax: +31-847-367881
E-Mail: info@chemtechniek.nl
Website: www.chemtechniek.nl

Description: Thi

This tape is a grey foamed acrylic adhesive tape with a special composition giving excellent all-round bonding properties and unique characteristics that give very high performance in the most demanding of applications.

Applications: Suitable for fixing corrugated roofs, repair of

traffic signs, adhering to irregular surfaces,

good adhesion on glass, aluminium,

galvanised steel.

Features: High cohesion, good adhesion.

Technical data:

Adhesive acrylic, foam

Thickness 1,1mm (±0,1mm)

Colour Grey Release liner LDPE

Adhesion 100 N/25mm Specific weight 750 kg/m³

Tensile strength 27 N/25mm (AFERA 4004)

Water resistance good (24 months in water)
Solvent resistance no changes (3 cycles, 20sec)

Temp. Performance -20° / +90C°

Recommended application-temperature

Range 10°C / 30°C

Important

When stored in the original packaging at 21° C and at 45-50% relative humidity the product has a shelf life of 12 months. Prior to use carefully check that the contact surfaces are totally dry and clean from oil, grease and dust. The data above correspond to the average values of the tests carried out according to Afera. The tests have been made on samples selected from our production. These data may vary without any notice.

Each product of ChemTechniek Nederland BV is warranted to be suitable for the specialized application for which it is intended. Since the methods and conditions of application are vital factors in the satisfactory performance of such factors are beyond our control, our warranty is limited to the refund of a specific product found by our company to be defective. The products of ChemTechniek Nederland BV are designed to serve such a wide variety of specialized applications that it is not practical include instructions for all uses. Special information furnished on request.